



MEDICAL 15Watts Desk Top Series



MODEL NO. GS2D-015

Dimension : 96mm (L)x43.6mm (W)x30mm (H)



INPUT REQUIREMENTS

- Input Range 100 to 240 VAC
- Frequency 50 to 60Hz
- Input Current $\leq 0.5A$
- Ripple:1%
- Efficiency >73%

OUTPUT REQUIREMENTS

- Output Range :DC5V- 24V
- Output Current : 15W Max

PROTECTION

- Over Current Protection Auto Recovery
- Short Circuit Protection

ENVIRONMENTAL

- Operating Temperature 0 to 40°C
- Storage Temperature -20 to 60 °C
- Storage Humidity 5 % to 95%
- MTBF >100,000 Hours at 25°C

SAFETY

- UL60601-1 CAN/CSA-C22.2
- EN60601-1 CB IEC60601-1
- FCC CE CB
- EMI FCC47 CFR Part15 Subpart EN55011

Model No.	Output Power(W)	Output voltage(Vo)	Output Current	Model No.	Output Power(W)	Output voltage(Vo)	Output Current
CS2D-015-05	15W	5V	3.0 A	CS2D-015-15	15W	15V	1.0 A
CS2D-015-06	15W	6V	2.5 A	CS2D-015-16	15W	16V	0.93A
CS2D-015-07	15W	7V	2.14A	CS2D-015-17	15W	17V	0.88A
CS2D-015-08	15W	8V	1.87A	CS2D-015-18	15W	18V	0.83A
CS2D-015-09	15W	9V	1.66A	CS2D-015-19	15W	19V	0.78A
CS2D-015-10	15W	10V	1.5 A	CS2D-015-20	15W	20V	0.75A
CS2D-015-11	15W	11V	1.36A	CS2D-015-21	15W	21V	0.71A
CS2D-015-12	15W	12V	1.25A	CS2D-015-22	15W	22V	0.68A
CS2D-015-13	15W	13V	1.15A	CS2D-015-23	15W	23V	0.65A
CS2D-015-14	15W	14V	1.07A	CS2D-015-24	15W	24V	0.62A