



LED 三段式省電調光 Driver

專利產品

產品特性:

- 由壁面開關做開切三段選擇亮度，調光更快速，更精準。
- 不需更改電源裝配線路，燈具更換更方便，安裝更省時。
- 不需外加調光旋鈕，零故障，低風險，更經濟。
- 輸入電壓95V~250VAC使用更便利，庫存管理很輕鬆。
- 可大面積調光控制，不受調光器功率限制，更安全，更穩定。
- 人性化的三段選擇更省電，更環保。

Product Features :

- Use as light ordinarily in general. Light up power failure immediately.
- Not necessary to change power supply assembly line. It is more convenient to replace the lamp and timesaving when install the lamp.
- Dimming button free, no breakdowns, low-risk and economical.
- The input voltage 95V~250VAC; that easy use and easy for stock management.
- Large area dimming control. Without any limitation by dimmer power. It's much safe and stable.
- Humanity three setting. High Efficiency and green lifestyle.

LED 三段式省電調光Driver

- 開關切換操作停頓時間2~4秒

產品型號 Model	功率 W Power W	輸出電壓範圍 Output voltage range	輸出電流範圍 Output Current range	功率因數 Power Factor	定電壓/定電流 Constant voltage / constant current	產品壽命 Product life MIL-HDBK-217F(25°C)
KID-3006-0300	110~220V	2~12W	DC 36V	12W.6W.2W	>40KHz	20000Hrs
KID-0048-0350	110~220V	2~18W	DC 48V	18W.10W.3W	>40KHz	20000Hrs
KID-0036-0600	110~220V	4~22W	DC 36V	22W.13W.4W	>40KHz	20000Hrs
KID-0024-0800	110~220V	4~20W	DC 24V	20W.16W.4W	>40KHz	20000Hrs
HID-0030-1200	110~220V	7~36W	DC 30V	36W 25W 7W	>40KHz	20000Hrs

以上僅為基本參考規格 另可延伸其他規格