



AC / DC 12Watts Wall Mount USB Series

With safety certificate and meet Energy Star Level V & ErP Stage 2 regulations and RoHS compliance.



Dimension :

- Case Size: 73.6mm (L)x28.5mm (W)x42.5mm (H)
- AC Plug: USA,EU,AS,UK

Input

- Input Range 100 to 240 VAC
- Frequency 50 to 60Hz
- Input Current $\leq 0.5A$
- Inrush Current $\leq 60A$
- Efficiency 75% Typ.

Output

- Over Voltage Protection Auto Recovery
- Over Current Protection Auto Recovery
- Short Circuit Protection Auto Recovery

Environmental

- Operating Temperature 0 to 40°C
- Storage Temperature -20 to 85 °C
- Storage Humidity 5 % to 95%

Safety

- UL/CUL , FCC,TUV/GS ,CE,CB, PSE, EN/IEC 60950

MTBF

50,000 hours minimum



UL 美日台



EU 歐洲



AS 澳洲



UK 英國

Model No.	Output Power(W)	Output voltage(Vo)	Output Current
GS2x-012-050-U	10W	5.0V	2.0A
GS2x-012-075-U	10W	7.5V	1.3A
GS2x-012-090-U	10W	9.0V	1.0A
GS2x-012-120-U	12W	12.0V	1.0A