

	MODEL NO.	CG2412-B719NMF IW	SHEET NO	1
	DESCRIPTION	SWITCHING MODE AC ADAPTER	ISSUED DATE: REVISED DATE:	2011/06/28


APPROVAL SIGNATURE
DATE:

Customer:

Model: CG2412-B719NMF(2A0F)IW

REV:00

AC Input	100-240Vac	DC Output	12V/2.0A	SC /
DC O/P cable	2468 20# 5.5*2.1*11mm 180°	音叉+KINK 5FT BLACK		
AC plug	美規 2PIN	Packaging	小白盒(95*51*95mm)	
To choose	☐ 轉廠			☒ 異地結轉 & 出口



* 參考用 *

亞達特科技股份有限公司

2F.-5, No.315, Sec. 3, Minsheng Rd., Banqiao Dist., New Taipei City 220, Taiwan
TEL: 02-22587990 FAX: 02-22586990

	MODEL NO.	CG2412-B719NMF IW	SHEET NO	3
	DESCRIPTION	SWITCHING MODE AC ADAPTER	ISSUED DATE:	2011/06/28
			REVISED DATE:	

CONTAINS:

INTRODUCTION

1.0INPUT REQUIREMENTS

- 1.1 Voltage (VAC)
- 1.2 Frequency
- 1.3 In-rush Current
- 1.4 Ac Input Current

2.0OUTPUT REQUIREMENTS

- 2.1 Output Power
- 2.2 Output Regulation
 - 2.2.1 Input Voltage
 - 2.2.2 Input Frequency
 - 2.2.3 Static Load
 - 2.2.4 Output Voltage
 - 2.2.5 Ripple
- 2.3 Transient Response and Deviation
- 2.4 Turn on, Hold up Time
- 2.5 Efficiency

3.0PROTECTION

- 3.1 Input Current
- 3.2 Over Voltage Protection
- 3.3 Over Current Protection
- 3.4 Short Circuit Protection

4.0MECHANICAL

- 4.1 Introduction
- 4.2 General Requirements
- 4.3 Power Supply Dimensions
- 4.4 Input / Output Connection
- 4.5 Unit Color

5.0RELIABILITY AND QUALITY CONTROL

- 5.1 MTBF
- 5.2 Burn-In

6.0ENVIRONMENTAL CONDITIONS

- 6.1 Non-operating
 - 6.1.1 Ambient Temperature
 - 6.1.2 Relative Humidity
- 6.2 Operating
 - 6.2.1 Ambient Temperature

	MODEL NO.	CG2412-B719NMF IW	SHEET NO	4
	DESCRIPTION	SWITCHING MODE AC ADAPTER	ISSUED DATE:	2011/06/28
			REVISED DATE:	

6.2.2 Relative Humidity

7.0EMI EMISSIONS

8.0SAFETY

8.1 Dielectric Strength (Hi-Pot) Test

8.2 Insulation Resistance

8.3 Leakage current

9.0 ENVIRONMENTAL PROTECTION

9.1 RoHS and WEEE

9.2 EPA /CEC and MEPS

10.0 PACKAGING

11.0 OUTLOOKING

12.0 SAFETY CERTIFICATES

	MODEL NO.	CG2412-B719NMF IW	SHEET NO	5
	DESCRIPTION	SWITCHING MODE AC ADAPTER	ISSUED DATE: REVISED DATE:	2011/06/28

INTRODUCTION

This documents specifies ONE voltage +12V power supply for electronic data processing equipment. The power supply will provide power to all system components.

1.0 INPUT REQUIREMENTS

- 1.1 Input Voltage Designing Range: 90~264 VAC.
- 1.2 Line Frequency Designing Range: 47 HZ to 63 HZ.
- 1.3 In-Rush Current: 30 A max. less under 115V conditions. Interruption of the input voltage for duration sufficient to cause the output voltage to drop below the regulation setting shall cause reactivation of in rush limiting capability. (Full-load 25°C Cold-start)
- 1.4 Input Current: 0.6 A max. at any line voltage specified in 2.1 at output full load condition.

2.0 OUTPUT REQUIREMENTS

2.1 Output Power (Rated Power)

The unit total output power from all voltage under steady state condition will not exceed 24 watts

2.2 Output Regulation

Label Information per Safety Agencies according to UL1950 and or EN60950 Requirements.

2.2.1 Input Rated Voltage Range: 100~240 VAC.

2.2.2 Line Rated Frequency: 50 HZ to 60 HZ.

2.2.3 Static Load

TABLE 2.2.3

Output	Voltage	Minimum Load	Maximum Load	Surge Current
1	+12V	0A	2.0A	-----

2.2.4 Output Voltage

The output voltage shall be statically regulated for all combinations of load (min./ max.), line and environment, including cross regulation (if any)as shown:

TABLE 2.2.4

Output	Voltage	Range	Tolerance
1	+12V	+11.4V~+12.6V	-5%,+5%

NOTE: Test measurement will be made at the output connector on the power Supply output cord and well connected on the mating connector.

2.2.5 Ripple and Noise

Differential ripple and noise at the power supply output shall be as shown below when measured under constant load range of 0.01~2.0A with an oscilloscope with at bandwidth of 20MHz.

	MODEL NO.	CG2412-B719NMF IW	SHEET NO	6
	DESCRIPTION	SWITCHING MODE AC ADAPTER	ISSUED DATE: REVISED DATE:	2011/06/28

TABLE 2.2.5

Output	Voltage	Maximum peak to peak ripple and noise
1	+12V	120mV($V_{in} \geq 100V_{ac}$)

NOTE: Test measurement will be made at the output connector on the power Supply output cord. With used an aluminum Electrolytic capacitor of 10uf and ceramic of 0.1uf parallel on output terminal can prevent unknown noise pick up.

2.3 Transient Response and Deviation

The load regulation for +12V is less than +/-10% while the measuring was done by changing the measured output loading from +20% to +80% of rated load .

2.4 Turn on, Hold up Time

During turn on and turn off, no voltage shall exceed its nominal voltage by more than 10% and no output will change its polarity with respect to its return line. All outputs shall reach their steady state values within 2 seconds of turn on and the hold up time for the output must be at least 10 mS tested at 110VAC/50HZ input with 80% maximum load on output.

2.5 Minimum Average Efficiency In Active

82.09% min. measured at I/P: 115Vac/60Hz or 230Vac/50Hz & Active Loading: 25%/50%/75%/100%

$[0.0626 \times \ln (\underline{12V \times 2A}) + 0.622] * 100\% = \underline{82.09\%}$ (Criteria : Level V)

3.0 PROTECTION

3.1 Input Current

An input fuse with a rating of 2A/250V Amps, shall be provided to protect the power supply and the input wiring. Note: The fuse shall be an unchangeable unit.

3.2 Over Voltage Protection (OVP)

The power supply shall shut down output when short primary feedback component.

3.3 Over Current Protection (OCP)

Overload conditions shall cause both the output current and the output voltages to decrease. Removal of an output overload conditions shall permit automatic recovery of the output voltage. The over current protection point Maximum=200% for all outputs.

Note: The total output power should not over Rated power to operate, otherwise will caused the power supply to damage.

3.4 Short Circuit Protection (SCP)

The power supply shall be protected from damage of accidentally short on the output terminal.

	MODEL NO.	CG2412-B719NMF IW	SHEET NO	7
	DESCRIPTION	SWITCHING MODE AC ADAPTER	ISSUED DATE:	2011/06/28
			REVISED DATE:	

4.0 MECHANICAL

4.1 Introduction

The power supply will provide

Output power connector show as in

Table 4.1

FRONT VIEW OF OUTPUT CONNECTOR

Table 4.1 Pin out for DC Connector

PIN	Output Voltage
	

4.2 General Requirements

The power supply must not exceed an audible noise level of 32 dB while operating under any combination of specified load and input voltages and frequencies. This noise level shall be measured according to IEC standards 651 type 1, with the sound level meter pointed directly at the power supply in a free-field condition, at a distance of 1 meter and by selecting nominal “A” weighting frequency attenuation.

4.3 Power Supply Dimensions

The dimensions of the power supply are shown: (75*35*55mm)

4.4 Input / Output Connection

AC PLUG	美規 2PIN
DC OUTPUT	2468 20# 5.5*2.1*11mm 180° 音叉+KINK 5FT BLACK

4.5 Unit Color: BLACK

5.0 RELIABILITY AND QUALITY CONTROL

5.1 Reliability

The design and construction of this power supply shall exhibit a minimum mean time between failure of 300,000 hours full rated load operation at 25.0°C, According to Telcordia SR-332, Issue 2.

5.2 Burn-in

The power supply will be performed 100% burn-in at 40°C (±5°C) under 80%-100% of full load on all power supplies.

6.0 ENVIRONMENTAL CONDITIONS

6.1 Storage

The power supply shall be capable of withstanding the following environmental conditions for extended periods of time, without sustaining electrical and/or mechanical damage and subsequent operational deficiencies:

6.1.1 Ambient temperature: -25°C ~ +85°C

	MODEL NO.	CG2412-B719NMF IW	SHEET NO	8
	DESCRIPTION	SWITCHING MODE AC ADAPTER	ISSUED DATE:	2011/06/28
			REVISED DATE:	

6.1.2 Relative Humidity: 10% ~ 95%

6.2 Operation

The power supply shall be capable of operating continuously in any mode without performance deterioration in the following environmental conditions:

6.2.1 Ambient Temperature: 0℃ ~ 40℃

6.2.2 Relative Humidity: 10% ~95%.

7.0 EMI EMISSIONS

The power supply meets the radiated and conducted emission requirements for a FCC part 15B class B(DoC)

8.0 SAFETY

The power supply must be certified or meet of the following safety standards:

	Certified	Meet
UL	★	
CUL or CSA	★	
PSE	★	
BSMI	★	
FCC	★	

8.1 Dielectric Strength (Hi-Pot) Test System:

Withstand AC 3 K V/10mA, for 2 sec./ min., primary to secondary.

8.2 Insulation Resistance:

Primary to secondary: 10 M OHM at 500 VDC.

8.3 Leakage current: $\leq$ 0.25mA

9.0 ENVIRONMENTAL PROTECTION

9.1 RoHS and WEEE

This product from design to production all the parts and process should meet the requirement of Restriction of the use of certain hazardous substances in electrical and electronic equipment RoHS directive 2002/95/EC and also meet the directive 2002/96/EC of Waste electrical and electronic equipment (WEEE) .


9.2 EPA /CEC and MEPS

To meet the energy saving trend, this product has designed to meet the American EPA energy star program for the EPS regulation , or requirement of CEC 400-2006-002, AS/NZS/4665.2.2005 for Australia and New Zealand.

10.0 PACKAGING: 小白盒(95*51*95mm)


	MODEL NO.	CG2412-C719NM IW	SHEET NO	13
	DESCRIPTION	SWITCHING MODE AC ADAPTER	ISSUED DATE:	2012/02/27
			REVISED DATE:	

11.0 OUTLOOKING



	MODEL NO.	CG2412-D1140NMIV IW	SHEET NO	12
	DESCRIPTION	SWITCHING MODE AC ADAPTER	ISSUED DATE:	2012/04/11
			REVISED DATE:	

11.0 OUTLOOKING



	MODEL NO.	CG2412-E719NM IW	SHEET NO	12
	DESCRIPTION	SWITCHING MODE AC ADAPTER	ISSUED DATE:	2012/03/01
			REVISED DATE:	

11.0 OUTLOOKING

