



AC / DC 5Watts USB Wall Mount

With safety certificate and meet Energy Star Level V & ErP Stage 2 regulations and RoHS compliance.



Dimension :

- UL Case Size: 41mm (L)x30mm (W)x20.5mm (H)
- UL Case Size: 59.67mm (L)x42.1mm (W)x20.2mm (H)

Input Requirements

- Input Range 100 to 240 VAC
- Frequency 50 to 60Hz
- Input Current $\leq 0.15A$

Output Requirements

- Output Voltage :5V DC 1.0A
- Ripple and Noise :350Mv
- Efficiency : 68.17%
- Hold up Time: 10 mS

Protection

- Over Voltage Protection Auto Recovery
- Over Current Protection Auto Recovery
- Short Circuit Protection Auto Recovery

Environmental

- Operating Temperature 0 to 40°C
- Storage Temperature -25 to 85 °C
- Storage Humidity 10% to 95%

Safety

- UL, FCC,TUV/GS ,CE, PSE,BSMI EN/IEC 60950

| Model No. | Output Power(W) | Output voltage(Vo) | Output Current |
|---------------|-----------------|--------------------|----------------|
| JTA1207 (UL) | 5W | 5V | 1.0A |
| JTA1207E (EU) | 5W | 5V | 1.0A |

ADT Technology Co., Ltd Tel:886-2-22587990#10 Fax:886-2-22586990